

**RENAULT
TRAFIC**



3rd October 2023

01. interior trims

02. equipment

03. engines

04. dimensions

01. interior trims



advance



extra (advance +)



extra sport (extra +)

02. equipment

advance

technology

- EASY LINK display with 8" touchscreen, DAB radio, Bluetooth and USB ports
- 4.2" colour TFT driver information display
- key - 3 button folding with selective opening
- 12v power socket (front)
- 6 speed gearbox with gear shift indicator
- ECO mode button
- wireless smartphone replication
- wireless smartphone integration with Android Auto™ and Apple CarPlay™

interior

- driver's seat with armrest - height adjustable, lumbar adjustment
- 'Kompo' upholstery
- electric front windows
- interior cabin lighting
- steering wheel - reach and rake adjustment
- dashboard with geometric grain
- front passenger bench seat
- closed glove box
- manual air conditioning with pollen filter

exterior

- full LED headlights with C-shaped DRL
- 16" steel wheel trims
- door mirrors - heated with electric adjustment and external temperature sensor
- left side loading door - unglazed
- rear doors - unglazed, 180°
- 80-litre fuel tank
- 20-litre AdBlue tank
- spare wheel with anti-theft spare wheel holder
- roof bar fixings
- body coloured door rail and rear tail light column with chrome grille

safety and security

- Alarm - Thatcham T1 volumetric alarm
- ESC (Electronic Stability Control) with Hill Start Assist and Grip Xtend
- anchorage points: 14 for Short wheel base (SWB) and 16 for Long wheel Base (LWB) weight allowed per anchorage ring: approximately 500kg
- airbag - driver
- full steel bulkhead with load-through facility
- wide view mirror (blind spot mirror in passenger sunvisor)
- rear parking sensors
- seatbelt reminder - driver and passenger

- seatbelts - 3 point height-adjustable seatbelts with pretensioners and load limiters
- deadlocking
- ABS with EBD (Electronic Brake force Distribution)
- remote central locking
- electronic immobiliser
- 4 disc brakes
- cruise control with speed limiter

new standard equipment across the range:

- active emergency braking
- driver attention alert
- lane departure warning
- tyre pressure detection
- airbag - front lateral, curtain and front passenger with deactivation
- traffic sign recognition

crew van adds:

- 2nd row of 3 passenger bench seat
- glazed bulkhead
- left and right side loading doors - glazed
- front passenger bench seat with underseat storage
- interior side panels up to windows

extra (advance +)

technology

- EASY LINK navigation with 8" touchscreen, DAB radio, Bluetooth and USB ports
- connected navigation services - 3 years included: Google search for places of interest, live traffic info and weather
- automatic headlights and rain sensitive front wipers

interior

- premium dashboard with horizontal grain and chrome styling
- premium faux leather steering wheel
- 'Java' upholstery
- interior LED cabin lighting

exterior

- 17" alloy wheels
- body coloured front and rear bumper, door mirrors and side mouldings (not available on Crew Van)
- door mirrors - electric folding

safety and security

- front fog lights
- automatic high beam
- handsfree key card with stop/start function

crew van adds:

- 2nd row of 3 passenger seats:
- individual seats with adjustable headrests, ISOFIX (left & right seat), 2 armrests and underseat storage
- left and right side loading doors - glazed with opening windows

extra sport (extra +)

interior

- climate control

exterior

- metallic paint
- 17" alloy wheels with black inserts

safety and security

- rear parking camera
- adaptive cruise control
- 360 parking sensors - front, rear and lateral ultra-sonic sensors

03. engines

	Blue dCi 130	Blue dCi 150	Blue dCi 150 Auto EDC	Blue dCi 170 Auto EDC
engine capacity/number of cylinders/ valves	1997/4/16	1997/4/16	1997/4/16	1997/4/16
max. power kW ECC (hp) at rpm	96 (130) at 3500	110 (150) at 3500	110 (150) at 3500	125 (170) at 3500
max. torque Nm ECC at rpm	320 at 1500	350 at 1500	350 at 1500	380 at 1500
type of injection	common rail direct injection (2500 bar)			
fuel and tank volume (L)	diesel - 80			
Adblue® fuel tank volume ⁽¹⁾ (L)	24.7			
emission control standard	Euro 6 d-full			
gearbox type	manual gearbox	manual gearbox	automatic gearbox dual clutch	automatic gearbox dual clutch
number of gears	6			
maintenance interval	up to 24,000 miles/2 years ⁽²⁾			
performance				
top speed (mph)	109	109	110	115
0-62 mph (s)	14.3	tbc	11.6	10.6
fuel consumption and emissions ⁽³⁾				
certification cycle				
combined fuel consumption (mpg)	40.9-40.4	40.4-40.9	40.4	39.8
CO ² emissions (g/km)	181-183	182-184	184-185	186-187
steering				
turning circle between kerbs (m)	short wheelbase: 12.4 - Long wheelbase: 13.8			
turning circle between walls (m)	short wheelbase: 12.8 - Long wheelbase: 14.3			
braking				
ABS with EBD (Electronic brake force distribution)	standard			
front: ventilated disks - Rear: solid disks Ø/width (mm)	296/28 - 280/12			
tyres				
tyre/wheel size	standard : 205/65 R16 option : 215/60 R17"		standard : 215/65 R16 option : 215/60 R17"	

- = not available.. (1) homologation in progress. The actual consumption of fuel and AdBlue depends on the conditions of use of the vehicle, the equipment, the driving style of the driver and the load. (2) an engine consumes oil for lubricating and cooling its moving parts. it is normal to top up the oil once or several times between two changes. (3) WLTP figures shown are for comparability purposes. Actual real-world driving results may vary depending on factors such as weather conditions, driving styles, vehicle load or any accessories fitted after registration. Depending on options fitted WLTP figures may differ. Please consult with local dealer or refer to www.business.renault.co.uk/configurator for more information. (4) WLTP (Worldwide harmonized Light vehicles Test procedures): this new protocol makes it possible to obtain results much closer to those observed during the daily trips carried out than the NEDC protocol.

04. dimensions

L1H1 Van / L2H1 Van

H1 van dimensions (mm)	L1H1	L2H1
maximum load volume (m ³)	5,8	7,75
exterior dimensions		
overall length	5 080	5 480
overall width with/without door mirrors	1956/2283	1956/2283
overall height	1971	1967
wheelbase length	3 098	3 498
front overhang	1014	1014
rear overhang	968	968
loading area		
width x length of the load-through facility	510 x 222	510 x 222
loading length on floor	2 537	2 937
loading length on floor (including load-through facility)	2 950	3 350
loading length on floor (including load-through facility into footwell)	3 750	4 150
loading length 400mm from the floor	tbc	2 937
loading length 1m from the floor	tbc	2 650
maximum loading area width	1662	1662
width between wheel arches	1268	1268
maximum loading area height	1387	1387
sliding side door(s)		
sliding side door entry width 600mm from the floor	907	907
sliding side door entry 100mm from the floor	1030	1030
sliding side door entry height	1284	1284
dimensions H1 van (mm)		
rear door		
entry width 70mm from the floor	1391	1391
entry height	1320	1320
loading sill	552	552
ground clearance	160	160
H1 van weights and loads (kg)		
version		
	SL30	LL30
gross vehicle weight	2 900 - 3 010	3 010-3 070
kerb weight	1783 - 2 066	1819 - 2102
max payload	1227	1251
max load on front axle	1625	1625
max load on rear axle	1650	1650
Max towable weight		
braked/unbraked manual	750/2 000 - 2 500	750/2 000 - 2 500
max towable weight		
braked/unbraked Auto EDC	750/1 690 - 1800	750/1630 - 1690

04. dimensions

L1H2 Van / L2H2 Van

H2 van dimensions (mm)	L1H2	L2H2
maximum load volume (m ³)	6,7	8,9
exterior dimensions		
overall length	5 080	5 480
overall width with/without door mirrors	1956/2283	1956/2283
overall height	2 495	2 498
wheelbase length	3 098	3 498
front overhang	1 014	1 014
rear overhang	968	968
loading area		
width x length of the load-through facility	510 x 222	510 x 222
loading length on floor	2 537	2 937
loading length on floor (including load-through facility)	2 950	3 350
loading length on floor (including load-through facility into footwell)	3 750	4 150
loading length 400mm from the floor	2 537	2 937
loading length 1m from the floor	2 250	2 650
maximum loading area width	1 662	1 662
width between wheel arches	1 268	1 268
maximum loading area height	1 898	1 898
sliding side door(s)		
sliding side door entry width 600mm from the floor	907	907
sliding side door entry 100mm from the floor	1 030	1 030
sliding side door entry height	1 284	1 284
dimensions H2 van (mm)		
rear door		
entry width 70mm from the floor	1 391	1 391
entry height	1 820	1 820
loading sill	552	552
ground clearance	160	160
H2 van weights and loads (kg)		
version		
gross vehicle weight	SH30	LH30
kerb weight	2 900	3 010
max payload	1 943 - 1 965	1 978 - 2 001
max load on front axle	935 - 957	1 009 - 1 032
max load on rear axle	1 625	1 625
max towable weight (braked/unbraked manual)	1 650	1 650
	750/2 500	750/2 500

04. dimensions

Crew Van

dimensions (mm)	LL30
load volume (m ³)	4.0
exterior dimensions	
wheelbase	3,498
overall length	5,480
front overhang	1,014
rear overhang	968
overall width with/without door mirrors	2,283/1956
width between wheel arches	1,268
loading area	
loading area length at 400mm from the floor	1,819
loading area length at floor	2,314 - 2,423
width * length of the opening under passenger bench seat	225*1220
maximum loading area width	1,662
sliding side door(s)	
sliding door sill width at 600mm from the floor	907
sliding door sill width at 100mm from the floor	1,030
sliding door sill height	1,284
rear door	
loading sill height (unladen)	552
ground clearance	160

weights (kg)	Advance	Extra		Extra Sport	
	Blue dCi 130	Blue dCi 150	Blue dCi 150 Auto	Blue dCi 150	Blue dCi 170 Auto
gross vehicle weight	3,070	3,070	3,070	3,070	3,070
gross train weight	5,570	5,570	4,700	5,570	4,700
maximum payload*	881	1,013	988	1,012	987
roof payload	200		200		200
kerb weight*	2,039	2,057	2,082	2,058	2,083
1° axle kerb weight (Kg)	1,306	1,306	1,331	1,306	1,331
2° axle kerb weight (Kg)	840	840	840	840	840
max weight on front axle	1,625	1,625	1,625	1,625	1,625
max weight on rear axle	1,650	1,650	1,650	1,650	1,650
braked trailer capacity	2,500	2,500	1,630	2,500	1,630
unbraked trailer capacity	750	750	750	750	750